
NS-27

Frosted Flat Lens with Clear Center

TRIM DIMENSIONS



Trim OD: 5" Height: 1-5/8"

FEATURES

<u>Trim</u>

High grade frosted flat lens with clear center attached to metal trim.

Mounting

Trim includes three trim clips that securely mount trim in housing.

Compatible Housings

Compatible with Line Voltage housings.

See individual specification sheets for more information.

Lamp

Line Voltage

50W R20/PAR20 Max. (NS-401QAT; NSIC-401QAT; NSR-404QAT)


Labels and Listings

cULus Listed for Wet Location when used with compatible housing.


ENORALIGHTING.

Type Project Catalog No. Lamp/Wattage


HOUSING DIMENSIONS



NSIC-401QAT



NSR-404QAT



Frosted Flat Lens with Clear Center and Metal Trim

| NS-27B: Frosted Flat Lens with Clear Center and Black Metal Trim |
|--|
| NS-27BZ: Frosted Flat Lens with Clear Center and Bronze Metal Trim |
| NS-27C: Frosted Flat Lens with Clear Center and Chrome Metal Trim |
| NS-27CO: Frosted Flat Lens with Clear Center and Copper Metal Trim |
| NS-27G: Frosted Flat Lens with Clear Center and Gold Metal Trim |
| NS-27N: Frosted Flat Lens with Clear Center and Natural Metal Trim |

NS-27W: Frosted Flat Lens with Clear Center and White Metal Trim

Compatible Housings

6505 Gayhart St., Commerce, CA 90040 www.noralighting.com • Specifications subject to change without notice. © 2011 Phone: 800.686.6672 • FAX: 800.500.9955 • e-mail: nora@noralighting.com

| LINE VOLTAGE | | | | |
|---------------|-------------------------------|-------------|--------------------------------|--|
| Item Number | Installation Type | Lamp | Dimensions | |
| ■ NS-401QAT | Non-IC Air-Tight New Const. | 50W R/PAR20 | W: 5-5/8" L: 8-1/2" H: 5-5/8" | |
| ■ NSIC-401QAT | IC Air-Tight New Construction | 50W R/PAR20 | W: 5-1/4" L: 8-1/2" H: 6-3/8" | |
| ■NSR-404QAT | Non-IC Air-Tight Remodel | 50W R/PAR20 | W: 4-1/4" L: 11-1/4" H: 5-5/8" | |

