


**NL-497
Metropolitan Ice Light Glass with White Trim**

TRIM DIMENSIONS



Trim OD: 5"
Height: 2-1/4"

FEATURES

Trim

Metropolitan Ice Light Glass with open center is mounted onto metal trim. Trim ring may also be used with custom combination of plastic or metal ring finishes.

Mounting

Trim includes three trim clips that securely mount trim in housing.

Compatible Housings

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

Lamp

Line Voltage (MR16 GU10)

50W 120V MR16 GU10 Max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)

Line Voltage (PAR16)

45W PAR16 Max. (NS-401QAT; NSIC-401QAT; NSR-404QAT)

Low Voltage

20W-50W 12V MR16 (NL-401 Series; NL-402 Series; NLIC-401 Series; NLIC-402 Series; NLR-403 Series; NLR-404 Series; NLR-405 Series)

Labels and Listings

cULus Listed for Damp Location when used with compatible housing.

IMPORTANT:

DO NOT USE GLASS LENS WHEN ALREADY USING LAMP w/ GLASS COVER

Metropolitan Ice Light Glass with White Trim

- NL-497B: Blue Metropolitan Ice Light Glass with White Trim
- NL-497F: Frosted White Metropolitan Ice Light Glass with White Trim
- NL-497P: Pink Metropolitan Ice Light Glass with White Trim

Type

Project

Catalog No.

Lamp/Wattage

Compatible Housings

LINE VOLTAGE (MR16 GU10)

Item Number	Installation Type	Lamp	Dimensions
<input type="checkbox"/> NSL-401AT/10	Non-IC Air-Tight New Const.	50W MR16	W: 5-5/8" L: 8-1/2" H: 5-3/4"
<input type="checkbox"/> NSLIC-401AT/10	IC Air-Tight New Construction	50W MR16	W: 8" L: 12-5/8" H: 8"
<input type="checkbox"/> NSLR-404AT/10	Non-IC Air-Tight Remodel	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"

LINE VOLTAGE (PAR16)

Item Number	Installation Type	Lamp	Dimensions
<input type="checkbox"/> NS-401QAT	Non-IC Air-Tight New Const.	45W PAR16	W: 5-5/8" L: 8-1/2" H: 5-3/4"
<input type="checkbox"/> NSIC-401QAT	IC Air-Tight New Construction	45W PAR16	W: 5-1/4" L: 8-1/2" H: 6-3/8"
<input type="checkbox"/> NSR-404QAT	Non-IC Air-Tight Remodel	45W PAR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"

LOW VOLTAGE

<input type="checkbox"/> NL-401QAT/20	Non-IC AT New Const., Mag.	20W MR16	W: 6" L: 9" H: 5-1/2"
<input type="checkbox"/> NL-401QAT/37	Non-IC AT New Const., Mag.	37W MR16	W: 6" L: 9" H: 5-1/2"
<input type="checkbox"/> NL-401QAT	Non-IC AT New Const., Mag.	50W MR16	W: 6" L: 9" H: 5-1/2"
<input type="checkbox"/> NL-401/50/277AT	Non-IC AT New Const., Mag.	50W MR16	W: 6" L: 9" H: 5-1/2"
<input type="checkbox"/> NL-401AT/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 6" L: 9" H: 5-1/2"
<input type="checkbox"/> NL-401AT/2EL	Non-IC AT New Const., Elec.	50W MR16	W: 6" L: 9" H: 5-1/2"
<input type="checkbox"/> NL-401/75	Non-IC AT New Const., Mag.	50W MR16	W: 7" L: 11-1/2" H: 6-3/8"
<input type="checkbox"/> NL-401/75/277	Non-IC AT New Const., Mag.	50W MR16	W: 7" L: 11-1/2" H: 6-3/8"
<input type="checkbox"/> NL-401/75/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 7" L: 11-1/2" H: 6-3/8"
<input type="checkbox"/> NL-401/75/2EL	Non-IC AT New Const., Elec.	50W MR16	W: 7" L: 11-1/2" H: 6-3/8"
<input type="checkbox"/> NL-402S/20	Non-IC Shallow New Con., Mag.	20W MR16	W: 6" L: 8-1/2" H: 3-1/2"
<input type="checkbox"/> NL-402S/37	Non-IC Shallow New Con., Mag.	37W MR16	W: 6" L: 8-1/2" H: 3-1/2"
<input type="checkbox"/> NL-402S	Non-IC Shallow New Con., Mag.	50W MR16	W: 6" L: 8-1/2" H: 3-1/2"
<input type="checkbox"/> NL-402S/1EL	Non-IC Shallow New Con., Elec.	50W MR16	W: 6" L: 8-1/2" H: 3-1/2"
<input type="checkbox"/> NLIC-401QSAT/20	IC Air-Tight New Const., Mag.	20W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
<input type="checkbox"/> NLIC-401QSAT/37	IC Air-Tight New Const., Mag.	37W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
<input type="checkbox"/> NLIC-401QSAT	IC Air-Tight New Const., Mag.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
<input type="checkbox"/> NLIC-401AT/277V	IC Air-Tight New Const., Mag.	50W MR16	W: 10-3/4" L: 17-3/4" H: 7-1/2"
<input type="checkbox"/> NLIC-401AT/1EL	IC Air-Tight New Const., Elec.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
<input type="checkbox"/> NLIC-401AT/2EL	IC Air-Tight New Const., Elec.	50W MR16	W: 7-3/4" L: 12-1/2" H: 7-1/4"
<input type="checkbox"/> NLIC-402QSAT/20	IC Air-Tight Shallow NC, Mag.	20W MR16	W: 13-1/8" L: 14" H: 5-3/8"
<input type="checkbox"/> NLIC-402QSAT/37	IC Air-Tight Shallow NC, Mag.	37W MR16	W: 13-1/8" L: 14" H: 5-3/8"
<input type="checkbox"/> NLIC-402QSAT	IC Air-Tight Shallow NC, Mag.	50W MR16	W: 13-1/8" L: 14" H: 5-3/8"
<input type="checkbox"/> NLIC-402AT/1EL	IC Air-Tight Shallow NC, Elec.	50W MR16	W: 13-1/8" L: 14" H: 5-3/8"
<input type="checkbox"/> NLR-403S/20	Non-IC Shallow Remodel, Mag.	20W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
<input type="checkbox"/> NLR-403S/37	Non-IC Shallow Remodel, Mag.	37W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
<input type="checkbox"/> NLR-403S	Non-IC Shallow Remodel, Mag.	50W MR16	W: 4-7/8" L: 13-1/2" H: 3-1/2"
<input type="checkbox"/> NLR-403S/1EL	Non-IC Shallow Remodel, Elec.	50W MR16	W: 4-7/8" L: 11-3/4" H: 3-1/2"
<input type="checkbox"/> NLR-404QAT/20	Non-IC Air-Tight Remodel, Mag.	20W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
<input type="checkbox"/> NLR-404QAT/37	Non-IC Air-Tight Remodel, Mag.	37W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
<input type="checkbox"/> NLR-404QAT	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
<input type="checkbox"/> NLR-404/50/277	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
<input type="checkbox"/> NLR-404AT/1EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
<input type="checkbox"/> NLR-404AT/2EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-7/8" L: 14-1/2" H: 5-5/8"
<input type="checkbox"/> NLR-404/75	Non-IC Remodel, Magnetic	50W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
<input type="checkbox"/> NLR-404/75/277	Non-IC Remodel, Magnetic	50W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
<input type="checkbox"/> NLR-404/75/1EL	Non-IC Remodel, Electronic	50W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
<input type="checkbox"/> NLR-404/75/2EL	Non-IC Remodel, Electronic	50W MR16	W: 4-7/8" L: 14-1/2" H: 6-3/8"
<input type="checkbox"/> NLR-405AT/20	Non-IC Air-Tight Remodel	20W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"
<input type="checkbox"/> NLR-405AT/37	Non-IC Air-Tight Remodel	37W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"
<input type="checkbox"/> NLR-405AT	Non-IC Air-Tight Remodel	50W MR16	W: 4-3/4" L: 4-3/4" H: 4-1/4"