

Type \_\_\_\_\_  
 Project \_\_\_\_\_  
 Catalog No. \_\_\_\_\_  
 Lamp/Wattage \_\_\_\_\_

**NX-503-LED**

**LED Exit Sign**

Lamp: (12) LED Modules 2VA (total)

**PRODUCT DESCRIPTION**

Nora Lighting's compact, low profile LED exit signs are as brilliant and visible as standard incandescent signs, yet use a fraction of the power. LED light sources require no maintenance for 25 years—saving greatly on maintenance and upkeep costs. Nora Lighting's LED exits are ideal for commercial and industrial standard non-emergency applications where low maintenance and operating costs are a must.

Universal 120V/277V exit sign utilizing Light Emitting Diode (LED) modules as the primary light source for economy operation.

**BODY**

- 12-1/8" Width X 8-3/4" Height X 1-3/4" Depth
- Injection-molded thermoplastic housing

**FACE**

- 6" high text with color diffusion
- Replaceable knockout directional chevrons
- Alternate "SALIDA" lettering available

**MOUNTING**

- Wall, side, or ceiling
- Mounting hardware and canopy included

**ELECTRICAL**

- 120V/277V Input
- Total power usage: 2 Watts
- 12 X LED units
- Short Circuit/ Surge protection

**LIFE EXPECTANCY**

- LED sources and PC circuitry are rated for a minimum of 25 years with no change in illumination level

**APPROVALS**

- UL 924
- NFPA
- NEC
- State & Municipal


**LIFE EXPECTANCY**

- Spare Lens, Red . . . .NEXL-R
- Spare Lens, Green . . .NEXL-G
- Plastic Shield . . . . .NEXS-P1
- Metal Shield . . . . .NEXS-M1



**DIMENSIONS**

**NX-503-LED**



**LED Exit Sign**

Catalog No.	Housing	Lens Color
<input type="checkbox"/> NX-503	(Blank) = White	<input type="checkbox"/> R = Red
	<input type="checkbox"/> B = Black	<input type="checkbox"/> G = Green
	<input type="checkbox"/> S = Salida	

Create a complete track head number: Example: NX-503BR