A19-15-E26-840-DIM



Prepared By:		Date:		
Driver Info		LED Info		
Watts	16W	Input Voltage	120V	
Color Temp	4000K (Cool White)	Power Factor	≥0.7	
Lumens	1,600	Flicker	N/A	
Efficacy	103.2 LPW	THDi	N/A	
Color Accurac	cy 80 CRI	R9		
L70 Accuracy	15,000			

Technical Specifications

Listings	Lamp Type:	LED Characteristics
UL Listed:	A Series Bulb	Lifespan:
Yes	Bulb Type:	15,000-hour LED lifespan based on IES LM-70 results
FCC:	A19	Other
Yes	Base Type:	Equivalent:
Rohs:	E26, Medium Screw Base	100W Incandescent A19
Yes	Material:	Warranty:
CEC Status:	Plastic	3 years
Not lawful for sale in California	Construction	Optical
ENERGY STAR V2.0:	Operating Temparture:	Beam Angle:
This product is ENERGY STAR® Version 2.0 Certified	-20 - 45°C	230°
Energy Star ID:	MOL (inches):	Shipping Information
2329688	4.57"	Case Qty:
Description	MOD (inches):	12
Dimmable:	2.36"	
Yes, down to 10%		

Technical Specifications (continued)				
Shipping Information	Pallet Quantity of Pieces:	Pallet Dimensions:		
Case Dimensions:	2016	47.24 x 39.37 x 45.67		
15.4 x 5.2 x 4.9				

A19-15-E26-840-DIM

Dimensions

Features

A-LINE REPLACEMENT - Replacement for conventional halogen and incandescent bulbs

ENERGY SAVINGS - Save up to 85% on energy

DAMP RATED - Suitable for damp locations

15,000-HOUR LIFESPAN - Last up to 13.7 years at 3 hours per day

ENCLOSED FIXTURE RATED - May be used in both enclosed and open fixtures

SHATTERPROOF - Plastic lamps for rugged applications

80 CRI - Ideal for general lighting applications

DIMMABLE - Compatible with most common dimmer models *100W Dimmable A Lamps can only be used in open fixture

2 3/8" 60mm
4 9/16" 116mm

Ordering Matrix

Family	Lamp Power	Base Type	CRI	Color Temp	Dimmable
A19	15	E26	8	40	DIM
	5 = 40W	E26 = E26	8 = 80 CRI	27 = 2700K	DIM = Dimmable
	9 = 60W	GU24 = GU24		30 = 3000K	
	10 = 60W			40 = 4000K	
	13 = 75W			50 = 5000K	
	15 = 100W				
	16 = 100W				