PS25-32-E26-840-ND 120-277V

Warranty

For Use in Emergency Fixtures

For Use Outdoors in Open Fixtures

RAB Lamps

Project:	Туре:	Prepared By:	Date:
	UPC: 19813833972	UNIVERSAL BULBS - Repla incandescent lamps operate UNIVERSAL voltage bulbs h and commercial applications ENERGY SAVINGS - Save of ENCLOSED FIXTURE RATH open fixtures DAMP RATED - Suitable for SHATTERPROOF - Plastic of applications	ave high lumen packages for industrial up to 85% on energy ED - May be used in both enclosed and
Technical Specifica Product Type Bulb Shape Wattage Wattage Equivalency Typical Lumen Output Efficacy Color Temperature CRI Base Type	tions A-Line PS25 E26 31.5W 300WW Incandescent 4100 128 Im/W 4000K Cool White 80 E26	Electrical Characteristics Input Voltage Power Factor Operating Frequency Input Current @ 120V Input Current @ 277V THDi Listings	120-277V >0.9 60 Hz 330mA 143mA ≤25%
Base Type L70 Lifespan Operating Temperature Dimmable Beam Angle	E26 40,000 hours -20°C - 45°C No 230°	UL Listed Yes UL Classified Yes	ul for sale in California

5-Year, No-Compromise Warranty

No

No

Case and Pallet Dimensions

	QTY	LENGTH	WIDTH	HEIGHT
CASE	12	10.8	8.3	14.4
PALLET	720	44.9	43.3	44.5

