

|                 |              |                     |              |
|-----------------|--------------|---------------------|--------------|
| <b>Project:</b> | <b>Type:</b> | <b>Prepared By:</b> | <b>Date:</b> |
|-----------------|--------------|---------------------|--------------|



**Features and Benefits**

- UNIVERSAL BULBS - Replace 60W, 125W, 200W and 300W incandescent lamps operated on 120V or 277V
- UNIVERSAL VOLTAGE - Bulbs have high lumen packages for industrial and commercial applications
- ENERGY SAVINGS - Save up to 85% on energy
- ENCLOSED FIXTURE RATED - May be used in both enclosed and open fixtures
- DAMP RATED - Suitable for damp locations
- SHATTERPROOF - Plastic constructed bulbs are ideal for rugged applications

| Technical Specifications          |                                | Electrical Characteristics |                                   |
|-----------------------------------|--------------------------------|----------------------------|-----------------------------------|
| Product Type                      | A-Line                         | Input Voltage              | 120-277V                          |
| Bulb Shape                        | A19 E26                        | Power Factor               | 0.8                               |
| Wattage                           | 8.5W                           | Operating Frequency        | 60 Hz                             |
| Wattage Equivalency               | 60WW Incandescent              | Input Current @ 120V       | 108mA                             |
| Typical Lumen Output              | 800                            | Input Current @ 277V       | 42mA                              |
| Efficacy                          | 94 lm/W                        | <b>Listings</b>            |                                   |
| Color Temperature                 | 2700K Soft White               | UL Listed                  | Yes                               |
| CRI                               | 80                             | CEC Status                 | Not lawful for sale in California |
| Base Type                         | E26                            |                            |                                   |
| L70 Lifespan                      | 25,000 hours                   |                            |                                   |
| Operating Temperature             | -20°C - 45°C                   |                            |                                   |
| Dimmable                          | No                             |                            |                                   |
| Beam Angle                        | 230°                           |                            |                                   |
| Warranty                          | 3-Year, No-Compromise Warranty |                            |                                   |
| For Use in Emergency Fixtures     | No                             |                            |                                   |
| For Use Outdoors in Open Fixtures | No                             |                            |                                   |

## Case and Pallet Dimensions

|        | QTY  | LENGTH | WIDTH | HEIGHT |
|--------|------|--------|-------|--------|
| CASE   | 12   | 5.2    | 4.9   | 15.4   |
| PALLET | 2268 | 48.1   | 47.3  | 39.8   |

## Dimension

