

Project: Type: Prepared By: Date:



Features and Benefits

OMNIDIRECTIONAL - HID lamp replacement from 70W up to 150W

UNIVERSAL voltage and compact design allows for installation across many applications.

 $\ensuremath{\mathsf{INSTALLATION}}$ ORIENTATION - Lamps can be installed base up, down, or horizontal

DAMP RATED - Suitable for use outdoors

BALLAST BYPASS- Reduces maintenance costs

ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures

120-277V

>0.9

60 Hz

330mA

143mA

≤25%

Technical Specifications

 Product Type
 HID

 Bulb Shape
 PS25

 Wattage
 31.5W

 Wattage Equivalency
 150W HID

 Typical Lumen Output
 4100

 Efficacy
 128 lm/W

Color Temperature 4000K Cool White

 CRI
 80

 Base Type
 EX39

 L70 Lifespan
 50,000 hours

 Operating Temperature
 -20°C - 45°C

Dimmable No Beam Angle 230°

Warranty 5-Year, No-Compromise Warranty

Installation Orientation Universal Installation

For Use in Emergency Fixtures No
For Use Outdoors in Open Fixtures No

urs UL Listed

UL Listed Yes UL Classified Yes

Electrical Characteristics

Input Voltage

Power Factor

THDi

Listings

Operating Frequency

Input Current @ 120V

Input Current @ 277V

This product is on the Design Lights Consortium (DLC)
DLC Listed Qualified Products List and is eligible for rebates from

DLC Member Utilities.

DLC Model Number A10030
DLC Product Code PNBF884R

CEC Status Lawful for sale in California



Case and Pallet Dimensions

	QTY	LENGTH	WIDTH	HEIGHT
CASE	12	12.2	8.3	16.2
PALLET	540	50	43.3	38.2

