

Project: _____ Type: _____ Prepared By: _____ Date: _____



Features and Benefits

OMNIDIRECTIONAL - HID lamp replacement from 70W up to 150W

UNIVERSAL voltage and compact design allows for installation across many applications.

INSTALLATION ORIENTATION - Lamps can be installed base up, down, or horizontal

DAMP RATED - Suitable for use outdoors

BALLAST BYPASS- Reduces maintenance costs

ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures

Technical Specifications

Product Type	HID
Bulb Shape	PS25
Wattage	31.5W
Wattage Equivalency	150W HID
Typical Lumen Output	4000
Efficacy	125 lm/W
Color Temperature	3000K Warm White
CRI	80
Base Type	EX39
L70 Lifespan	50,000 hours
Operating Temperature	-20°C - 45°C
Dimmable	No
Beam Angle	230°
Warranty	5-Year, No-Compromise Warranty
Installation Orientation	Universal Installation
For Use in Emergency Fixtures	No
For Use Outdoors in Open Fixtures	No

Electrical Characteristics

Input Voltage	120-277V
Power Factor	>0.9
Operating Frequency	60 Hz
Input Current @ 120V	330mA
Input Current @ 277V	143mA
THDi	≤25%

Listings

UL Listed	Yes
UL Classified	Yes
DLC Listed	This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities.
DLC Model Number	A10029
DLC Product Code	P78BZPH6
CEC Status	Lawful for sale in California

Case and Pallet Dimensions

	QTY	LENGTH	WIDTH	HEIGHT
CASE	12	12.2	8.3	16.2
PALLET	540	50	43.3	38.2

Dimension

