PS25-32-EX39-850-ND 120-277V

Color Temperature

Operating Temperature

Installation Orientation

For Use in Emergency Fixtures

For Use Outdoors in Open Fixtures

CRI

Base Type

Dimmable

Warranty

Beam Angle

L70 Lifespan

| Project: | Туре: | Pr | epared By: | Date: |
|----------------------------|--------------------------|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| U LISTED | RAB VICE 19813834016 | RoHSI Compliant | OMNIDIRECTIONAL - HIE UNIVERSAL voltage and o across many applications. INSTALLATION ORIENTA down, or horizontal DAMP RATED - Suitable f BALLAST BYPASS- Redu | TION - Lamps can be installed base up, |
| Technical Specification | | | | |
| Product Type Bulb Shape | HID PS25 | Electrical Characteristics | | |
| Vattage | 2525 31.5W | Input Voltage | | 120-277V |
| Vattage Equivalency | 150W HID | Power Factor Operating Frequency | | >0.9 |
| ypical Lumen Output | 4100 | | | 60 Hz |
| Efficacy | 128 lm/W | Input Current @ 120V | | 330mA |
| | | Input Current @ 277V | | 143mA |

Input Current @ 277V

DLC Model Number A10031

DLC Product Code PIZZZAZV

Yes

Yes

DLC Member Utilities.

Lawful for sale in California

THDi

Listings

UL Listed

UL Classified

DLC Listed

CEC Status

5-Year, No-Compromise Warranty

5000K Daylight

50,000 hours

-20°C - 45°C

Universal Installation

80

No

No

No

230°

EX39

143mA

≤25%

This product is on the Design Lights Consortium (DLC)

Qualified Products List and is eligible for rebates from

RAB

PS25-32-EX39-850-ND 120-277V

Case and Pallet Dimensions

Dimension

