

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Produces rich and vibrant colors >90CRI
- Energy efficient replacement for incandescent and halogen lamps
- Constructed from durable plastic which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Frosted lens produces smooth diffuse light
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, Title 20 Compliant
- Dimmable with common dimmer types (check compatibility list)

Technical Specifications		
Performance	L70 Lifespan:	Warranty (Years):
Product Type: A-Line	25,000 Hours	RAB warrants that our LED products will be free from defects in materials and workmanship for a period of four (4) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty .
Input Wattage: 6W	Dimmable: Yes, down to 10%	Electrical
Typical Lumen Output: 450	Construction	Power Factor: 0.9
Efficacy: 75 lm/W	Bulb Shape: A19	Operating Temperature: -20°C - 45°C
Color Temperature: 3000K Warm White	Base Type: E26	Input Voltage: 120V
CRI: 90	Beam Angle: 230°	
	Other	
	Equivalency: 40W Incandescent	

Technical Specifications (continued)

Electrical

Operating Frequency:

60 Hz

Technical Specifications

For Use in Emergency Fixtures:

No

For Use Outdoors in Open Fixtures:

No

Electrical Characteristics

Flicker:

<30%

Compliance

UL Listed:

Yes

ENERGY STAR V2.0:

This product is ENERGY STAR® Version 2.0 Certified

Energy Star ID:

2330065


CEC Status:

Lawful for sale in California

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10	7.6	5.1
PALLET	3456	45.4	40	46.1

Dimension



Light Distribution

