

|                 |              |                     |              |
|-----------------|--------------|---------------------|--------------|
| <b>Project:</b> | <b>Type:</b> | <b>Prepared By:</b> | <b>Date:</b> |
|-----------------|--------------|---------------------|--------------|



**Features and Benefits**

- Produces rich and vibrant colors >90CRI
- Energy efficient replacement for incandescent and halogen lamps
- Constructed from durable plastic which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Frosted lens produces smooth diffuse light
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, Title 20 Compliant
- Dimmable with common dimmer types (check compatibility list)

| Technical Specifications                      |   |   |
|---|---|---|
| <b>Performance</b>                            | <b>L70 Lifespan:</b>                    | <b>Warranty (Years):</b>  |
| <b>Product Type:</b><br>A-Line                | 25,000 Hours                            | RAB warrants that our LED products will be free from defects in materials and workmanship for a period of four (4) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a> . |
| <b>Input Wattage:</b><br>9W                   | <b>Dimmable:</b><br>Yes, down to 10%    | <b>Electrical</b>   |
| <b>Typical Lumen Output:</b><br>800           | <b>Construction</b>                     | <b>Power Factor:</b><br>0.9   |
| <b>Efficacy:</b><br>84 lm/W                   | <b>Bulb Shape:</b><br>A19               | <b>Operating Temperature:</b><br>-20°C - 45°C   |
| <b>Color Temperature:</b><br>3000K Warm White | <b>Base Type:</b><br>E26                | <b>Input Voltage:</b><br>120V   |
| <b>CRI:</b><br>90                             | <b>Beam Angle:</b><br>230°              |   |
|   | <b>Other</b>                            |   |
|   | <b>Equivalency:</b><br>60W Incandescent |   |

## Technical Specifications (continued)

### Electrical

**Operating Frequency:**

60 Hz

### Technical Specifications

**For Use in Emergency Fixtures:**

No

**For Use Outdoors in Open Fixtures:**

No

### Electrical Characteristics

**Flicker:**

<30%

### Compliance

**UL Listed:**

Yes

**ENERGY STAR V2.0:**

This product is ENERGY STAR® Version 2.0 Certified

**Energy Star ID:**

2330070


**CEC Status:**

Lawful for sale in California

## Case and Pallet Dimensions

|               | QTY  | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|---------------|------|-------------|------------|-------------|
| <b>CASE</b>   | 12   | 10          | 7.6        | 5.2         |
| <b>PALLET</b> | 3456 | 45.4        | 40         | 47.1        |

## Dimension



## Light Distribution

