

<b>Project:</b>	<b>Type:</b>	<b>Prepared By:</b>	<b>Date:</b>
-----------------	--------------	---------------------	--------------



**Features and Benefits**

- Replacement for High output incandescent or Metal Halide and High Pressure Sodium HID Lamps
- Commercial Grade
- Large metal heatsink for optimal heat dissipation
- In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast
- Rated for use in enclosed and open fixtures in dry or damp locations
- Ideal for post top, bollards, and outdoor corridor lighting
- Environmentally friendly, no mercury used
- UL Listed, EnergyStar Listed
- Non-Dimmable
- Universal Voltage 120 through 277V
- 50,000 hour Lifespan
- 5 Year No Compromise Warranty

<b>Technical Specifications</b>		
<b>Performance</b>	<b>L70 Lifespan:</b>	<b>Warranty (Years):</b>
<b>Product Type:</b> A-Line	40,000 Hours	RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <a href="http://rablighting.com/warranty">rablighting.com/warranty</a> .
<b>Input Wattage:</b> 16.5W	<b>Dimmable:</b> No	<b>Electrical</b>
<b>Typical Lumen Output:</b> 2050	<b>Construction</b>	<b>Power Factor:</b> >0.9
<b>Efficacy:</b> 121 lm/W	<b>Bulb Shape:</b> A21 E26	<b>Operating Temperature:</b> -20°C - 45°C
<b>Color Temperature:</b> 5000K Daylight	<b>Base Type:</b> E26	<b>Input Voltage:</b> 120-277V
<b>CRI:</b> 80	<b>Beam Angle:</b> 230°	
	<b>Other</b>	
	<b>Equivalency:</b> 125WW Incandescent	

## Technical Specifications (continued)

### Electrical

#### Operating Frequency:

60 Hz

### Technical Specifications

#### For Use in Emergency Fixtures:

No

#### For Use Outdoors in Open Fixtures:

No

### Electrical Characteristics

#### Input Current @ 120V:

178mA

#### Input Current @ 277V:

77mA

#### THDi:

≤25%

### Compliance

#### UL Listed:

Yes

#### UL Classified:

Yes

#### CEC Status:

Not lawful for sale in California

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
<b>CASE</b>	12	5.9	6.1	17.5
<b>PALLET</b>	1176	43.7	45.7	36.2

## Dimension

