

**Project:**

**Type:**

**Prepared By:**

**Date:**



UPC: 019813833880



### Features and Benefits

Replacement for High output incandescent or Metal Halide and High Pressure Sodium HID Lamps

Commercial Grade

Large metal heatsink for optimal heat dissipation

In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast

Rated for use in enclosed and open fixtures in dry or damp locations

Ideal for post top, bollards, and outdoor corridor lighting

Environmentally friendly, no mercury used

UL Listed, EnergyStar Listed

Non-Dimmable

Universal Voltage 120 through 277V

50,000 hour Lifespan

5 Year No Compromise Warranty

### Technical Specifications

#### Performance

**Product Type:**

A-Line

**Input Wattage:**

16.5W

**Typical Lumen Output:**

2050

**Efficacy:**

121 lm/W

**Color Temperature:**

4000K Cool White

**CRI:**

80

**L70 Lifespan:**

40,000 Hours

**Dimmable:**

No

**Construction**

**Bulb Shape:**

A21 E26

**Base Type:**

E26

**Beam Angle:**

230°

**Other**

**Equivalency:**

125WW Incandescent

**Warranty (Years):**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Electrical**

**Power Factor:**

>0.9

**Operating Temperature:**

-20°C - 45°C

**Input Voltage:**

120-277V

## Technical Specifications (continued)

### Electrical

**Operating Frequency:**

60 Hz

### Technical Specifications

**For Use in Emergency Fixtures:**

No

**For Use Outdoors in Open Fixtures:**

No

### Electrical Characteristics

**Input Current @ 120V:**

178mA

**Input Current @ 277V:**

77mA

**THDi:**

≤25%

### Compliance

**UL Listed:**

Yes

**UL Classified:**

Yes

**CEC Status:**

Not lawful for sale in California

## Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
<b>CASE</b>	12	5.9	6.1	17.5
<b>PALLET</b>	1176	43.7	45.7	36.2

## Dimension

