

Project:

Type:

Prepared By:

Date:



UPC: 019813507453



Features and Benefits

Replaces CFL 18W, 26W, and 32W G24q Lamps

Ballast Compatible. Directly Compatible with Most Existing CFL Ballasts.

Compatible with G24q / GX24q (4-pin CFL) installations

50,000 hour Lifespan

Environmentally friendly, no mercury used

UL Listed, DLC Listed

Rated for use in enclosed and open fixtures in dry or damp locations

Non-Dimmable

5 Year No Compromise Warranty

Technical Specifications

Performance

Product Type:

Compact

Input Wattage:

9W

Efficacy:

100 lm/W

Color Temperature:

2700K Soft White

CRI:

82

L70 Lifespan:

50,000 Hours

Construction

Bulb Shape:

PLC

Base Type:

G24q

Technical Specifications

Finish:

Frosted

For Use Outdoors in Open Fixtures:

No

Electrical

Power Factor:

Ballast Dependent

Operating Frequency:

Ballast Dependent

Input Voltage:

Ballast Dependent

Other

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of six (6) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Installation

Installation Type:

Type A, Plug and Play

Electrical Characteristics

THDi:

<20%

Technical Specifications (continued)

Compliance

UL Listed:

Suitable for damp locations. Suitable for use in enclosed fixtures.

CEC Status:

Lawful for sale in California


Application:

Suitable for damp locations and totally enclosed fixtures.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	8.1	6.1	5.1
PALLET	2880	0	0	0

Wiring Diagram



Dimension

