

Project:

Type:

Prepared By:

Date:



UPC: 019813833873



Features and Benefits

Replacement for High output incandescent or Metal Halide and High Pressure Sodium HID Lamps

Commercial Grade

Large metal heatsink for optimal heat dissipation

In HID retrofit applications - Integral Driver enables lamp to be wired directly to line voltage. Must bypass ballast

Rated for use in enclosed and open fixtures in dry or damp locations

Ideal for post top, bollards, and outdoor corridor lighting

Environmentally friendly, no mercury used

UL Listed, ENERGY STAR Compliant

Non-Dimmable

Universal Voltage 120 through 277V

50,000 hour Lifespan

5 Year No Compromise Warranty

Technical Specifications

Performance

Product Type:

A-Line

Input Wattage:

16.5W

Typical Lumen Output:

2000

Efficacy:

118 lm/W

Color Temperature:

3000K Warm White

CRI:

80

L70 Lifespan:

40,000 Hours

Dimmable:

No

Construction

Bulb Shape:

A21 E26

Base Type:

E26

Beam Angle:

230°

Other

Equivalency:

125WW Incandescent

Warranty (Years):

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Electrical

Power Factor:

>0.9

Operating Temperature:

-20°C - 45°C

Input Voltage:

120-277V AC

Technical Specifications (continued)

Electrical

Operating Frequency:

60 Hz

Technical Specifications

For Use Outdoors in Open Fixtures:

No

Electrical Characteristics

Input Current @ 120V:

178mA

Input Current @ 277V:

77mA

THDi:

≤25%

Compliance

UL Listed:

Yes

UL Classified:

Yes

CEC Status:

Not lawful for sale in California

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	5.9	6.1	17.5
PALLET	1176	43.7	45.7	36.2

Dimension

