



Color: White

Weight: 15.1 lbs

Project:**Type:****Prepared By:****Date:****Driver Info**

Type	Constant Current
120V	0.34A
208V	0.20A
240V	0.17A
277V	0.15A
Input Watts	29.6-48.2W

LED Info

Watts	40W
Color Temp	Field Adjustable
Color Accuracy	79-82 CRI
L70 Lifespan	75,000 Hours
Lumens	3745-5365
Efficacy	110.4-126.5 lm/W

Technical Specifications**Field Adjustability****Field Adjustable:**

Field adjustable light output:
2' x 4': 30W/40W/50W (factory default 40W)
Color temperature (selectable by 3500K, 4000K and 5000K)

Compliance**UL Listed:**

Suitable for damp locations

IESNA LM-79 & IESNA LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: PL3725S1

Performance**Lifespan:**

75,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

LED Characteristics**LEDs:**

Long-life, high-efficacy, surface-mount LEDs

Construction**Ambient Operating Temperature:**

-30°C (-22°F) to 40°C (104°F)

Lens:

Frosted Polystyrene

Mounting:

Recessed ceiling

IC Rated:

Suitable for insulated ceilings

Housing:

Lightweight aluminum housing

Finish:

Formulated for high durability and long-lasting color

Green Technology:

Mercury and UV free. RoHS-compliant components.

Other**Warranty:**

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Technical Specifications (continued)

Other

Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Electrical

Driver:

Constant Current, Class 2, 120-277V, 50/60 Hz,
120V: 0.34A, 208V: 0.20A, 240V: 0.17A, 277V:
0.15A


THD:

8.51% at 120V, 8.95% at 277V

Power Factor:

99.3% at 120V, 95.2% at 277V

Dimensions



Features

- Field-adjustable light output (3 discrete steps)
- White tunable (3 discrete color temperatures)
- Can be changed before, during or after installation
- 75,000-Hour LED lifespan

Ordering Matrix

Family	Size	Voltage	Options
EZPANFA	2X4	/D10	
	1X4 = 1' x 4'	/D10 = 0-10V Dimming	Blank = No Option
	2X2 = 2' x 2'		/LC = Lightcloud® Controller
	2X4 = 2' x 4'		/LCS = Lightcloud® Sensor
			/E2 = Battery Backup