## A19-4-E26-922/30-WGD

Project:	Туре:	Prepared By:	Date:
			Features and Benefits
	UPC: 01.93E+11		
LISTED	FCC CA20	Low grant and a second and a se	

erformance	Dimmable:	Endcap Material:
roduct Type:	Yes	Polycarbonate
-Line	Compliance	Enclosure Material:
nput Wattage:	UL Listed:	Plastic
4.5W	Suitable for damp locations	Beam Angle:
Lumens (Nominal):	Enclosed Fixtures:	230°
450lm	Suitable for use in enclosed fixtures	Electrical
Efficacy:	LED Characteristics	THD:
100 lm/W	Color Temperature:	59.70%
Color Accuracy (CRI):	2200K/3000K	Power Factor:
>90 CRI	Construction	0.7
L70 Lifespan:	Bulb Shape:	
15,000-Hour LED lifespan based on IES LM-70 results	A19	
	Base Type:	
	E26	

RAB

## A19-4-E26-922/30-WGD

## **Technical Specifications (continued)** Electrical **Operating Frequency:** Wattage Equivalency: 60 Hz 40W Incandescent **Operating Temperature:** Other -20°C - 45°C Input Voltage: Warranty: 120V RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

## **Case and Pallet Dimensions**

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	9.8	7.4	9.8
PALLET	1500	48	40	22.72

