

Project: Type: Prepared By: Date:



UPC: 192552005999









#### **Features and Benefits**

Produces rich and vibrant colors >90CRI

Energy efficient replacement for incandescent and halogen Reflector lamps

Constructed from durable plastic which lowers risk of breakage

Rated for use in enclosed and open fixtures in dry or damp locations

Frosted lens produces smooth diffuse light

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

ENERGY STAR Compliant, Title 20 Compliant

Smooth warm to dim transition between 2200K to 3000K color temperatures  $\,$ 

Uniform dimming down to 10% (See Dimmer Compatibility List)

### **Technical Specifications**

Performance

**Product Type:** 

Reflector

Input Wattage:

5.5W

Lumens (Nominal):

500lm

Efficacy:

90.9 lm/W

Color Accuracy (CRI):

>90 CRI

L70 Lifespan:

15,000-Hour LED lifespan based on IES LM-70 results

Dimmable:

Yes

Compliance

**UL Listed:** 

Suitable for damp locations

**Enclosed Fixtures:** 

Suitable for use in enclosed fixtures

**LED Characteristics** 

**Color Temperature:** 

2200K/3000K

Construction

**Bulb Shape:** 

R20

**Base Type:** 

E26

**Endcap Material:** 

Polycarbonate

**Enclosure Material:** 

Plastic

Beam Angle:

110°

**Electrical** 

THD:

62.90%

**Power Factor:** 

0.7



# **Technical Specifications (continued)**

## **Electrical**

#### **Operating Temperature:**

-20°C - 45°C (-4°F - 113°F)

### Input Voltage:

120V

#### **Operating Frequency:**

60 Hz

#### Other

### Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty</u>.

#### Wattage Equivalency:

40W Halogen

## **Case and Pallet Dimensions**

|        | QTY  | LENGTH (in) | WIDTH (in) | HEIGHT (in) |
|--------|------|-------------|------------|-------------|
| CASE   | 12   | 10.6        | 8          | 10.6        |
| PALLET | 1140 | 48          | 40         | 22.72       |

