




Project:

Type:

Prepared By:

Date:



UPC: 019813510293



Features and Benefits

Replacement for traditional Metal Halide or High Pressure Sodium HID Lamps

Active Cooling: Internal sensor overheats and engaged will automatically reduce output to 70% rated wattage until the sensor cools and will light up again to 100%

Integral Driver enables lamp to be wired directly to line voltage without need for an external driver or ballast

Rated for use in enclosed and open fixtures in dry or damp locations

4kV surge protection built in

50,000 hour Lifespan

Environmentally friendly, no mercury used

UL Listed, UL Classified

5 Year No Compromise Warranty

Lamp includes on board low-voltage AUX port for lamp level sensor accessories

Compatible with RAB specified 0-10V dimming system

Technical Specifications

Performance

Product Type:

HID Replacement

Input Wattage:

80W

Lumens (Nominal):

10800lm

Efficacy:

135 lm/W

Color Accuracy (CRI):

80 CRI

L70 Lifespan:

50,000 Hours

Dimming:

Compatible with RAB specified 0-10V dimming system. Dimming capabilities were tested and verified on Legrand RH4FBL3PTC 0-10V dimming system.

Construction

Bulb Shape:

Post Top

Base Type:

EX39

For Use Outdoors in Open Fixtures:

Yes

Other

Equivalency:

320W HID

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found

LED Characteristics

Color Temperature:

4000K Cool White

Electrical

THD:

<20%

Power Factor:

>0.9

Operating Temperature:

-30°C - 60°C

Input Voltage:

100-277V



at rablighting.com/warranty.



Technical Specifications (continued)

Electrical

Operating Frequency:

50/60Hz

Input Current @ 120V:

0.89mA

Flicker:

<30%

Installation

Installation Type:

Type B, Ballast Bypass

Installation Orientation:

For Vertical Installation Only

Compliance

UL Listed:

Yes

UL Classified:

Yes

DLC Model Number:

HID-80-EX39-840-BYP-PT

CEC Status:

Lawful for sale in California

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

DLC Product Code: PLWSMNXFAPS


Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
9.8 x 9.8 x 9.1	1


Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	20.7	14.2	14
PALLET	18	30.3	43.3	46.7


Wiring Diagram



Dimension




Light Distribution





Sensor Installation



Compatible with:

HID-80-EX39-8xx-BYP-PT-G2
HID-100-EX39-8xx-BYP-PT-G2
HID-120-EX39-8xx-BYP-PT