



UPC: 192552007306



Weight: 0.0 lbs

Project:

Type:

Prepared By:

Date:

Technical Specifications

Performance

Product Type:

Compact

Input Wattage:

5.5W

Lumens (Nominal):

600lm

Efficacy:

109 lm/W

L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

Wattage Equivalency:

11W CFL

Compliance

UL Listed:

Suitable for damp locations

Enclosed Fixtures:

Suitable for use in enclosed fixtures

LED Characteristics

Color Temperature:

4000K

Color Accuracy (CRI):

≥80 CRI

Construction

Bulb Shape:

PLS-Horizontal

Base Type:

Gx23

Endcap Material:

Copper

Enclosure Material:

Polycarbonate

Features

- Replaces 13W CFL Lamps
- Plug and Play on existing magnetic CFL ballasts or can be wired directly to line voltage without need for an external driver or ballast
- Compatible with Gx23 base installations
- 50,000 hour Lifespan
- Environmentally friendly, no mercury used
- UL Classified
- Rated for use in enclosed and open fixtures in dry or damp locations
- 5 Year No Compromise Warranty

Ordering Matrix

Family		Wattage		Orientation		CRI/Color Temp		Installation Type	
PLS	–	5.2	–	H	–	840	–	HYB	
		3.5 = 3.5W 5 = 5W 5.2 = 5.2W		H = Horizontal		840 = 80 CRI, 4000K 835 = 80 CRI, 3500K 830 = 80 CRI, 3000K 827 = 80 CRI, 2700K		HYB = Hybrid	