A19-10-E26-930-F-C

RAB[®] Residential



Project:	Туре:
Prepared By:	Date:

Performance	Wattage Equivalency:	Dimmable:
Product Type:	75W Incandescent	Yes
-Line	Compliance	Flicker:
put Wattage:	Enclosed Fixtures:	<30%
WG	Suitable for use in enclosed fixtures	Operating Temperature:
umens (Nominal):	LED Characteristics	-20°C - 45°C (-4°F - 113°F)
,100 Lm	Color Temperature:	Input Voltage:
ficacy:	3000K	120V
0 Lm/W	Color Accuracy (CRI):	
70 Lifespan:	>90 CRI	
000-Hour LED lifespan based on IES LM-70 results	Electrical	
	Power Factor:	
	>0.7	

A19-10-E26-930-F-C

RAB[®] Residential

Technical Specifications (continue	d)	
Electrical	Endcap Material:	Other
Operating Frequency:	Nickel-Aluminum	Warranty:
50/60Hz	Enclosure Material:	RAB warrants that our LED products will be free from
Construction	Glass	defects in materials and workmanship for a period of three (3) years from the date of delivery to the end
Bulb Shape:	Optical	user, including coverage of light output, color
		stability, driver performance and fixture finish. RAB's

A19

Base Type:

E26 Edison

Endcap Material:
Nickel-Aluminum
Enclosure Material:
Glass
Optical
Beam Angle:
360°


ility, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.



	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	10.8	8.1	10.8
PALLET	1080	44.09	38.74	26.67



Features

Replacement for conventional decorative lamps

Filament LED construction gives a unique traditional look and feel for decorative and ambient applications

Produces rich and vibrant colors, >90CRI

Rated for use in enclosed and open fixtures in dry and damp locations

Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs

Title 20 Compliant, ENERGY STAR Compliant, UL Listed

Smooth uniform dimming down to 10% (See Dimmer Compatibility List)

A19-10-E26-930-F-C

	atrix				
Family	Wattage	Base Type	CRI/Color Temp	Туре	Finish
A19 –	10 -	- E26 -	- 930	– F ·	- C
	5 = 5W 9 = 9W 10 = 10W 13 = 13W	E26 = E26	950 = 90 CRI, 5000K 940 = 90 CRI, 4000K 930 = 90 CRI, 3000K 927 = 90 CRI, 2700K	F = Filament	C = Clear F = Frosted