



The SUMO offers a sleek, low-profile design that adds a modern look to any space. They are easy to install with field adjustable color temperature, affordable, and a stylish options for new construction or retrofit.

Color: White

Weight: 6.9 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	35W
120V	0.32A	Color Temp	2700/3000/3500/4000/5000K
208V	0.18A	Color Accuracy	90 CRI
240V	0.15A	L70 Lifespan	50,000 Hours
277V	0.14A	Lumens	2,600-2,850 lm
Input Watts	35W	Efficacy	74-81 lm/W

Technical Specifications

Performance	Electrical	LED Characteristics
Product Type: Edge-lit Surface Mount	Driver: Constant Current, Class 2, 50/60 Hz 120-277V, 120V: 0.32A, 208V: 0.18A, 240V: 0.15A, 277V: 0.14A	Color Temperature: Field Adjustable: 2700K,3000K,3500K,4000K,5000K
Input Wattage: 35W	THD: ≤20%	Color Accuracy (CRI): >90 CRI
Lumens: 5000K: 2,850lm 4000K: 2,810lm 3500K: 2,800lm 3000K: 2,650lm 2700K: 2,600lm	Power Factor: ≥0.9	R9 Value: High color performance with R9 greater than or equal to 50
Efficacy: 5000K: 81lm/W 4000K: 80lm/W 3500K: 80lm/W 3000K: 76lm/W 2700K: 74lm/W	Dimmable: Yes, 0-10V and TRIAC/ELV dims down to 10%. See Dimmer Compatibility List.	Color Consistency: 4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color
L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results	Input Voltage: 120-277V	Color Stability: LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period
Wattage Equivalency: Equivalent to 200W Incandescent	Operating Frequency: 50/60Hz	Color Uniformity: RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.
	Operating Temperature: -4°F to 104°F (-20°C to 40°C)	Installation
	Surge Protection: 2.5kV	Mounting: Surface Mount

Technical Specifications (continued)

Construction

Size:
24"

Shape:
Round

Finish:
Formulated for high durability and long-lasting color

Housing Material:
Metal

Trim Style:
Smooth

Lens:
Frosted lens constructed from polycarbonate material diffuses light evenly and smoothly

Compliance

Listings:
UL Listed

Environment:
Suitable for use in indoor and outdoor application in dry, damp, and wet environments

UV Protection:
Fade-resistant powder spray polyester

Energy Star Approved:
This product is ENERGY STAR® Version 2.2 Certified

California Energy Commission (CEC) Status:
Lawful for Sales in California

NEC Compliant:
Suitable for use in closets. Compliant with NEC Sec. 410.16 (A)(1) and 410.16 (C3).

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
Complies with Part 15B of the FCC Rules

Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

Other


Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Dimensions



Features

- Select from 5 field-adjustable color temperatures 5000K, 4000K, 3500K, 3000K, or 2700K
- Suitable for indoor/outdoor applications in dry, damp, or wet environments
- 0-10V and TRIAC/ELV dims down to 10%. See Dimmer Compatibility List
- Meets California Title 24 requirements
- 50,000-Hour LED lifespan
- 5-Year, No-Compromise Warranty
- 120V-277V