EZPANFA2X2/D10/E2



Color: White

Weight: 7.1 lbs

Project:	**Type:**
Prepared By:	**Date:**

Driver Info

Type	Constant Current
120V	0.25A
208V	0.15A
240V	0.13A
277V	0.12A
Input Watts	26.07-39.97W

LED Info

Watts	30W
Color Temp	3500/4000/5000K
Color Accuracy	81-84 CRI
L70 Lifespan	75,000 Hours
Lumens	3,372-5,252 lm
Efficacy	118.8-138.4 lm/W

Technical Specifications

Field Adjustability

Field Adjustable:
Field Adjustable Light Output:
2' x 2': 40W/30W/25W (factory default 30W)
Color temperature selectable by 3500K, 4000K and 5000K (factory default 4000K)

Compliance

UL Listed:
Suitable for damp locations

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

CCEA Compliant:
Luminaire Requirements used in Environmental Air Space per the electrical code specification of the City of Chicago

Trade Agreements Act Compliant:
This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

DLC Listed:
This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.
DLC Product Code: PB45PSA0

Performance

Lifespan:
75,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

LED Characteristics

LEDs:
Edge-lit design with long-life, high-efficacy LEDs

Electrical

Driver:
Constant Current, Class 2, 120-277V, 50/60 Hz, 120V: 0.25A, 208V: 0.15A, 240V: 0.13A, 277V: 0.12A

THD:
4.04% at 120V, 11.28% at 277V

Power Factor:
99.9% at 120V, 97% at 277V

Battery Backup:
Battery backup will operate the LED Lamp for 90 minutes if power fails. Wired for 120V-277V.

Construction

Operating Temperature:
-30°C (-22°F) to 40°C (104°F)

Lens:
Frosted polystyrene

Housing:
Lightweight aluminum housing

Finish:
Formulated for high durability and long-lasting color

Green Technology:
Mercury and UV free. RoHS-compliant components.

Installation

Mounting:
Recessed ceiling


Other

5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Copyright © 2025 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice

EZPANFA2X2/D10/E2

Dimensions



Features

- 100,000-hour LED Lifespan
- DLC Standard Listed
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family	Size	Wattage	Driver
EZPANFA	2X2	/D10	/E2
	2X2 = 2' x 2' **2X4 =** 2' x 4' **1X4 =** 1' x 4'	**2X4 =** 50/40/30W **1X4 =** 40/30/25W **2X2 =** 40/30/25W	**/D10 =** 0-10V Dimming **Blank =** 120-277V, 0-10V Dimming

Copyright © 2025 RAB Lighting All Rights Reserved Note: Specifications are subject to change at any time without notice