



S29563

4.5G25/CL/LED/E26/27K/120V
 4.5 watt G25 LED; Clear; Medium base; 2700K; 450 lumens;
 120 volts

Features

- LED with a traditional incandescent look and feel
- Omni-directional light source
- Smooth dimming
- Replaces up to 40 watt lamps
- Long life - 15,000 hours
- Damp Location
- UL listed for totally enclosed fixtures
- Shatterproof option available on request



S29563

| Item Number | UPC | Voltage | Watts | Incandescent Equivalent | Power Factor | Lamp Shape | Base |
|-------------|--------------|---------|-------|-------------------------|--------------|------------|--------|
| S29563 | 045923295638 | 120 | 4.5 | 40W | >0.70 | G25 | Medium |

| ANSI Base | Lamp Code | Dimmable/Non-Dimmable | Suggested Dimmers | Finish | MOL In Inches | MOD In Inches | Initial Lumens |
|-----------|----------------------------|-----------------------|-----------------------------------------------|--------|---------------|---------------|----------------|
| E26 | 4.5G25/CL/LED/E26/27K/120V | Dimmable | Compatible dimmers for S29563 | Clear | 4-3/8" | 3.13" | 450 |

| Average Rated Hours | Kelvin Temp | Color | CRI | Beam Spread Deg | Operating Temperature | Pack | Package Type |
|---------------------|-------------|------------|-----|-----------------|-----------------------------------------|------|--------------|
| 15000 | 2700 | Warm White | 80 | 360 | -20C (-4F) to a maximum of +45C (+113F) | 24/6 | Box |

| ENERGY STAR | CEC Status | RoHS Compliant | UL or ETL Listed | UL Classification | Warranty |
|-------------|------------------------------------------------------|----------------|------------------|-----------------------------|--------------------------------|
| ENERGY STAR | Non-Compliant Possible sub: S9878 | Yes | Yes | cULus - Damp Location Rated | 3 Year Limited |



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

