

Project Name

Location

Prepared By



SATCO S12101

5.5G16/LED/SW/3K/120V/E12

Notes

General

| | |
|-------------------------|--------------|
| Status | Active |
| Watts | 5.5 |
| Incandescent Equivalent | 60 |
| Volts | 120V |
| Shape | G16 |
| Base | Candelabra |
| ANSI Base | E12 |
| Finish | Frosted |
| CCT (Kelvin) | 3000 |
| Temperature | Warm White |
| CRI | 82 |
| Lumens | 500 |
| Beam Spread | 360 |
| Dimmable | Yes Dimmable |
| Hours Rated | 15000 |
| Technology | LED |

Electrical

| | |
|-----------------------|---|
| Operating Frequency | 60 Hz |
| Dimmable Down To | 19 |
| Power Factor | >0.7 |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

Physical

| | |
|--------------|------|
| MOL | 3.13 |
| MOD | 2 |
| Weight (lb.) | 0.05 |

Additional Information

| | |
|----------------------------|---------------------|
| Enclosure Rating | Enclosed Rated Lamp |
| Rated For Enclosed Fixture | Yes |
| Warranty | 3 Year Limited |

Compliance

| | |
|-----------------|---------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | Yes |
| ES Unique ID | ESID-2350169 |
| CEC Status | Non-Compliant |
| RoHS Compliant | Yes |
| SDS Sheet | LED_Lamp |