

SPECIFICATION SHEET

Omni-Directional Dimmable LED Lamp

Item Number 51950

Specifications

| Energy Used (Watts) | 11 |
|-------------------------------------------|-------------------------|
| Incandescent Equivalent Wattage | 75 |
| Domestic Code | 110MNIA19/LED/DIM/SW/27 |
| Volts | 120 |
| Brightness (Lumens) | 1100 |
| Average Rated Hours | 25,000 |
| Life (in years)* | 22.8 |
| Light Appearance (Kelvin) | 2700 |
| Beam Spread | 270° |
| CRI | 80 |
| Efficacy (LPW) | 100 |
| Number of LED Modules | 24 |
| Estimated Yearly Energy Cost** | \$1.32 |
| Package Type | Box |
| Can be used in totally enclosed fixtures. | |
| | |

Physical Characteristics

| Color Designation | Warm White |
|-------------------|------------------------|
| Finish | Soft White |
| Housing Material | Polycarbonate/Aluminum |
| Base | Medium |
| MOL | 4.49" |



This lamp is warranted to be free from defects in material and workmanship for 5 years (based on using 3 hours per day).

Warning

- Turn power off before inspection, installation, or removal.
- Risk of electric shock Do not use where exposed to water or weather.
- Do not open no user serviceable parts inside.
- · Suitable for Damp Locations The lamp is suitable for use in wet locations when used in an outdoor rated fixture.
- This device is not intended for use with emergency exit luminaires or emergency exit lights.
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with the limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Any changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.
- This lamp may not be compatible with all dimmers.
- * Based on 3 hrs./day
- ** Based on 3 hrs./day 11¢/kWh Cost depends on rates and use.

Specifications are subject to change without notice, please visit www.westinghouselighting.com for latest information.





OMNI-DIRECTIONAL LED Dimmer Compatibility

| Brand | Model |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Leviton | 1PE04-1LZ, C20-6681-IW, C22-6672-1LW, C26-RNL06-TW, C90-6683-IW, DDMX1-BLZ, DSL06-1LZ, IPI06-1LZ, IPL06-10Z, R50-6602-IW, R62-6674-POW |
| Lutron | 002-6633-PLW, AYCL-153P, AYLV-600P, CTCL-153P, D-600P, D-600PH, DV-603PG, DVCL-153P, DVELV-300P, DVLV-600P, MACL-153M, MAELV-600, MRF2-6CL-WH, MRF2-6ELV-120, MRF2-6ND-120, NLV-600, NTLV-600, PD-6WCL, Q-600P, RRD-10ND, S-600, S-600P, SCL-153P-WH, TGCL-153PH-WH, TTCL-100H-WH, VTELV-600M |

Call 1-800-999-2226 or visit www.westinghouselighting.com.

(W),WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation. Used under license by Westinghouse Lighting. All Rights Reserved.